



# IECEX Certificate of Conformity

## INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit [www.iecex.com](http://www.iecex.com)

Certificate No.:	<b>IECEX DEK 18.0082</b>	Page 1 of 4	<u>Certificate history:</u>
Status:	<b>Current</b>	Issue No: 3	<a href="#">Issue 2 (2020-06-25)</a>
Date of Issue:	2024-04-24		<a href="#">Issue 1 (2019-09-03)</a>
Applicant:	<b>RIKEN KEIKI Co., Ltd.</b> 2-7-6, Azusawa, Itabashi-ku, Tokyo, 174-8744, <b>Japan</b>		<a href="#">Issue 0 (2019-03-01)</a>
Equipment:	<b>Portable Gas Monitor model GW-3 (CMS-4 when marked for the Clemco Industries Corp.)</b>		
Optional accessory:			
Type of Protection:	<b>Ex i</b>		
Marking:	Ex ia IIC T4 Ga		

Approved for issue on behalf of the IECEx  
Certification Body:

**L.G. van Schie**

Position:

**Certification Manager**

Signature:  
(for printed version)

Date:  
(for printed version)

2024-04-24

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting [www.iecex.com](http://www.iecex.com) or use of this QR Code.



Certificate issued by:

**DEKRA Certification B.V.**  
Meander 1051  
6825 MJ Arnhem  
Netherlands





# IECEX Certificate of Conformity

Certificate No.: **IECEX DEK 18.0082**

Page 2 of 4

Date of issue: 2024-04-24

Issue No: 3

Manufacturer: **RIKEN KEIKI Co., Ltd.**  
2-7-6, Azusawa,  
Itabashi-ku,  
Tokyo, 174-8744,  
**Japan**

Manufacturing  
locations: **RIKEN KEIKI Co., Ltd.**  
2-3, Minamisakae-cho,  
Kasukabe-shi,  
Saitama, 344-0057,  
**Japan**

**RIKEN KEIKI NARA MFG. Co., Ltd.**  
49-1, Abe, Sakurai-shi,  
Nara, 633-0054,  
**Japan**

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEX Quality system requirements. This certificate is granted subject to the conditions as set out in IECEX Scheme Rules, IECEX 02 and Operational Documents as amended

#### STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

[IEC 60079-0:2017](#) Explosive atmospheres - Part 0: Equipment - General requirements  
Edition:7.0

[IEC 60079-11:2011](#) Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"  
Edition:6.0

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

#### TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

[NL/DEK/ExTR18.0075/03](#)

Quality Assessment Reports:

[NL/DEK/QAR23.0010/00](#)

[NL/DEK/QAR23.0011/00](#)



# IECEX Certificate of Conformity

Certificate No.: **IECEX DEK 18.0082**

Page 3 of 4

Date of issue: 2024-04-24

Issue No: 3

## **EQUIPMENT:**

Equipment and systems covered by this Certificate are as follows:

The Portable Gas Monitor model GW-3 (CMS-4 when marked for the Clemco Industries Corp.) is designed to provide continuous exposure monitoring of toxic gases and/or oxygen by diffusion sampling method.

Portable Gas Monitor is available either as a single gas monitor for measuring carbon monoxide (CO), hydrogen sulphide (H<sub>2</sub>S) or as dual gas monitor for measuring simultaneously (CO/O<sub>2</sub>) or (CO/H<sub>2</sub>).

Sensor types used are either electrochemical or galvanic type.

The measurement results are displayed on the LCD while gas alarms can be issued via LED and buzzer. Measurement results can be wirelessly transmitted to a host using IrDA.

The examination of the Portable Gas Monitor does not include a judgement of the functional performance of the apparatus.

Ambient temperature: -20 °C to +60 °C

## **Electrical data**

Supply:

User-replaceable primary lithium manganese button cell battery (3.7 V, 610 mAh).

**SPECIFIC CONDITIONS OF USE: NO**



# IECEX Certificate of Conformity

Certificate No.: **IECEX DEK 18.0082**

Page 4 of 4

Date of issue: 2024-04-24

Issue No: 3

**DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)**

1. Minor change on the label drawing.
2. Linked to new QARs.
3. Manufacturing location Ebina Denki is no longer listed.