



# IECEX Certificate of Conformity

## INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit [www.iecex.com](http://www.iecex.com)

Certificate No.:	<b>IECEX DEK 13.0024X</b>	Page 1 of 4	<u>Certificate history:</u>
Status:	<b>Current</b>	Issue No: 6	Issue 5 (2020-07-07)
Date of Issue:	2022-08-24		Issue 4 (2017-04-25)
Applicant:	<b>RIKEN KEIKI Co., Ltd.</b> 2-7-6, Azusawa, Itabashi-ku, Tokyo, 174-8744, <b>Japan</b>		Issue 3 (2016-05-12)
Equipment:	<b>Gas detector, Type SD-1EC, SD-1DEC, SD-1OX and SD-1DOX</b>		Issue 2 (2015-04-21)
Optional accessory:			Issue 1 (2014-11-20)
Type of Protection:	<b>Ex db</b>		Issue 0 (2014-01-21)
Marking:	Ex db IIC T6 Gb		

Approved for issue on behalf of the IECEx  
Certification Body:

**L.G. van Schie**

Position:

**Certification Manager**

Signature:  
(for printed version)

Date:  
(for printed version)

2022-08-24

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting [www.iecex.com](http://www.iecex.com) or use of this QR Code.



Certificate issued by:

**DEKRA Certification B.V.**  
**Meander 1051**  
**6825 MJ Arnhem**  
**Netherlands**





# IECEX Certificate of Conformity

Certificate No.: **IECEX DEK 13.0024X**

Page 2 of 4

Date of issue: 2022-08-24

Issue No: 6

Manufacturer: **RIKEN KEIKI Co., Ltd.**  
2-7-6, Azusawa,  
Itabashi-ku,  
Tokyo, 174-8744,  
**Japan**

Manufacturing  
locations: **RIKEN KEIKI Co., Ltd.**  
2-3, Minamisakae-cho,  
Kasukabe-shi,  
Saitama, 344-0057,  
**Japan**

**RIKEN KEIKI NARA MFG. Co., Ltd.**  
49-1, Abe, Sakurai-shi,  
Nara, 633-0054,  
**Japan**

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEX Quality system requirements. This certificate is granted subject to the conditions as set out in IECEX Scheme Rules, IECEX 02 and Operational Documents as amended

#### STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

[IEC 60079-0:2017](#) Explosive atmospheres - Part 0: Equipment - General requirements  
Edition:7.0

[IEC 60079-1:2014-06](#) Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"  
Edition:7.0

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

#### TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

[NL/DEK/ExTR13.0003/06](#)

Quality Assessment Report:

[NO/PRE/QAR19.0018/04](#)



# IECEX Certificate of Conformity

Certificate No.: **IECEX DEK 13.0024X**

Page 3 of 4

Date of issue: 2022-08-24

Issue No: 6

## **EQUIPMENT:**

Equipment and systems covered by this Certificate are as follows:

Gas Detectors, Type SD-1EC, SD-1DEC, SD-10X and SD-1DOX are fixed mount, continuous monitoring gas detectors providing a 4 to 20 mA output signal.

The detector consists of an aluminium enclosure with integral cable gland, a plastic window and a screwed-on aluminium or stainless steel sensor.

The sensor of Type SD-1EC and Type SD-10X monitors the surrounding atmosphere and is protected by a guard.

The sensor of Type SD-1DEC and Type SD-1DOX is protected by a cover with process connections to monitor the connected atmosphere at atmospheric pressure and a temperature not exceeding the ambient temperature range.

The examination of the gas detector does not include a judgement of the functional performance of the apparatus.

Ambient temperature range -20 °C to +60 °C.

### Electrical data

Supply: 24 Vdc, max. 45 mA

Analogue output: 24 Vdc, 4 - 20 mA (max. 22 mA) optional with HART communication

Contact output: max. 30 Vdc / 250 Vac, 0.5 A

### **SPECIFIC CONDITIONS OF USE: YES as shown below:**

- The plastic window is submitted to tests corresponding to the low risk of mechanical danger.
- The property class of the cover screws is at least A\*-70.
- The flameproof joints are not intended to be repaired.



# IECEX Certificate of Conformity

Certificate No.: **IECEX DEK 13.0024X**

Page 4 of 4

Date of issue: 2022-08-24

Issue No: 6

**DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)**  
Introduction of an alternative sensor for Type SD1OX and SD-1DOX