



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEX DEK 24.0012** Page 1 of 3 [Certificate history:](#)
Status: **Current** Issue No: 0
Date of Issue: 2024-06-26
Applicant: **RIKEN KEIKI Co., Ltd.**
2-7-6, Azusawa,
Itabashi-ku,
Tokyo, 174-8744
Japan
Equipment: **Portable Gas Detector model RX-8500, RX-8600 and RX-8700**
Optional accessory:
Type of Protection: **Ex i**
Marking: **Ex ia IIC T4...T3 Ga**

Approved for issue on behalf of the IECEx
Certification Body:

R. Schuller

Position:

Certification Manager

Signature:
(for printed version)

Date:
(for printed version)

2024-06-26

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

DEKRA Certification B.V.
Meander 1051
6825 MJ Arnhem
Netherlands





IECEX Certificate of Conformity

Certificate No.: **IECEX DEK 24.0012**

Page 2 of 3

Date of issue: 2024-06-26

Issue No: 0

Manufacturer: **RIKEN KEIKI Co., Ltd.**
2-7-6, Azusawa,
Itabashi-ku,
Tokyo, 174-8744
Japan

Manufacturing
locations: **RIKEN KEIKI Co., Ltd.**
2-3, Minamisakae-cho,
Kasukabe-shi,
Saitama, 344-0057,
Japan

RIKEN KEIKI NARA MFG. Co., Ltd.
49-1, Abe, Sakurai-shi,
Nara, 633-0054,
Japan

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEX Quality system requirements. This certificate is granted subject to the conditions as set out in IECEX Scheme Rules, IECEX 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

[IEC 60079-0:2017](#) Explosive atmospheres - Part 0: Equipment - General requirements
Edition:7.0

[IEC 60079-11:2011](#) Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"
Edition:6.0

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

[NL/DEK/ExTR24.0015/00](#)

Quality Assessment Reports:

[NL/DEK/QAR23.0010/01](#)

[NL/DEK/QAR23.0011/00](#)



IECEX Certificate of Conformity

Certificate No.: **IECEX DEK 24.0012**

Page 3 of 3

Date of issue: 2024-06-26

Issue No: 0

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The Portable Gas Detector Model RX-8500, RX-8600 and RX-8700 are gas monitors designed to provide continuous monitoring of exposure to combustible gas, oxygen (O₂), carbon monoxide (CO), carbon dioxide (CO₂) and hydrogen sulfide (H₂S) in hazardous areas. The air suction is automatically made using an internal micro pump. All the models are the same in construction except that there are differences in sensors and Model RX-8700 has one more pump for air suction.

Model RX-8500, RX-8600 or RX-8700 is combined with Battery Unit Model BUD-8000 or Model BUL-8000. Model BUD-8000 includes primary batteries and Model BUL-8000 includes secondary Li-ion battery. Replacement or charging of Battery Unit can be performed by end-users and is only allowed in non-hazardous areas.

For the temperature class, T4 is applied when combined with Model BUL-8000 or with Model BUD-8000 including batteries of LR6T(JE), Toshiba. T3 is applied when combined with Model BUD-8000 including batteries of MN1500, Duracell.

Ambient temperature range -20 °C to +50 °C

Ambient temperature range during charge 0 °C to +40 °C

Additional information

The performance of the Portable Gas Detector Model RX-8500, RX-8600 or RX-8700, as a safety device, is not covered by this certificate.

Electrical data

Supply: Battery Unit Model BUD-8000 with three series connected primary batteries, or Rechargeable Battery Unit Model BUL-8000.

Non-replaceable primary battery for backup.

Refer to manufacturer's instructions for the permitted battery types.

SPECIFIC CONDITIONS OF USE: NO