

# For accurate measurement of the concentration of a variety of types of gases

## **Optical Interferometric Gas Monitor**

## Model **FI-8000**

IECEx ATEX CE marking

#### Up to 8 types of gases can be measured with 1 unit

You can combine up to 8 types of your preferred gases. You can also add or change measurement target gases after purchase.

#### Continuous measurement mode / intermittent measurement mode supported

In addition to the usual continuous measurement mode, an intermittent measurement mode is available in which you can set an interval, so that you can record the gas concentration value and the time at intervals. (The intermittent measurement mode is only available with the automatic suction specification.)

#### **Two measurement methods**

The product has a lineup of an automatic suction type using the built-in pump and a manual suction type which enables faster suction using the handy aspirator.

#### **Protection class IP67 compliant**

IP67 compliance provides reassurance during outdoor work.

#### Easy-to-view, large LCD screen

With the large numeral and character display, you can check the gas concentration and perform operations smoothly.

#### Intrinsically safe explosion-proof structure

IECEx: Ex ia IIC T4 Ga ATEX: II 1 G Ex ia IIC T4 Ga



FI-8000

RIKEN KEIKI

### **RIKEN KEIKI Co., Ltd.**

#### The History of the Optical Interferometric Gas Monitor



frequently. To prevent the accidental explosions on oil tarkers occurred based on the principle of optical interference developed at Riken, and Riken Keiki was established for the purpose of productizing the detector. The productized detector came to be widely used in coal mines and for safety supervision.

The Riken type 3 gas detector was certified as an "analytical instrument and scientific instrument heritage" item by the Japan Analytical Instruments Manufacturers' Association (JAIMA) and the Japan Scientific Instruments Association (JSIA), as it was a valuable device that contributed to the lives of Japanese people.

Digital display	Reduced weight
Automatic analysis	Data logger function
IP67	Simple operation

#### 3 Specifications in Total



Regarding the gases detectable as standard in the anesthetic / fumigation gas specification, refer to "Measurement Target Gas List." For the customized specification, you can select up to 8 types of measurement target gases. Select from among identical chamber lengths (the "Measurement Target Gas List" column). In addition, for all the specifications, measurement target gases can be added or changed after purchase.

#### FI-8000 Model

For the FI-8000 optical interferometric gas monitor, select the suction method and measurement target gas to match your intended use. The selected specification is reflected in the model name as follows.



### Measurement Target Gas List

Chamber length 5 mm		
Measurement target gas	Base gas	Measurement range
Acatulara	Air	0 - 100 vol%
Acetylene	Nitrogen	0 - 100 vol%
Isobutane	Air	0 - 100 vol%
Ethylene	Air	0 - 100 vol%
Vinyl chloride	Nitrogen	0 - 100 vol%
Chlorine	Air	0 - 100 vol%
Xenon	Air	0 - 100 vol%
Dimethul ether	Air	0 - 100 vol%
Dimetnyi etner	Nitrogen	0 - 100 vol%
Hydrogen	Carbon dioxide	0 - 100 vol%
Carbon dioxide	Air	0 - 100 vol%
Normal butane	Air	0 - 100 vol%
Propane	Air	0 - 100 vol%
Freon 410A	Nitrogen	0 - 100 vol%
Freon 22	Air	0 - 100 vol%
Methyl bromide	Air	0 - 100 vol%
Sulfur hexafluoride	Air	0 - 100 vol%
	Air	0 - 99.9%up
	Nitrogen	0 - 100 vol%
Butane-air	-	0 - 134.25 MJ/m <sup>3</sup> Gross 0°C
	-	0 - 123.75 MJ/m <sup>3</sup> Net 0°C
Propane-air	_	0 - 101.35 MJ/m <sup>3</sup> Gross 0°C
	-	0 - 93.15 MJ/m³ Net 0°C

Regarding gases not included in the list, please make a separate inquiry with us.

Chamber length 24 mm		
Measurement target gas	Base gas	Measurement range
Isoflurane	Air	0 - 8 vol%
	Oxygen	0 - 8 vol%
Sevoflurane	Air	0 - 10 vol%
	Oxygen	0 - 10 vol%
Dooflurano	Air	0 - 20 vol%
Desilurarie	Oxygen	0 - 20 vol%
	Air	0 - 6 vol%
Talottalle	Oxygen	0 - 6 vol%
Nitrous oxide	Air	0 - 100 vol%
Acetylene	Nitrogen	0 - 50 vol%
Ethylene	Air	0 - 50 vol%
Enflurance	Air	0 - 10 vol%
Ennurane	Oxygen	0 - 10 vol%
Ozone	Oxygen	0 - 100 vol%
Difluoromethane	Nitrogen	0 - 100 vol%
	Air	0 - 100 vol%
Heavy hydrogen	Nitrogen	0 - 100 vol%
	Air	0 - 100 vol%
Hydrogen	Nitrogen	0 - 100 vol%
	Argon	0 - 100 vol%
	Air	0 - 100 vol%
Carbon dioxide	Nitrogen	0 - 100 vol%
	Argon	0 - 100 vol%
Neon	Air	0 - 100 vol%
Propane	Air	0 - 20 vol%
	Air	0 - 100 vol%
Helium	Nitrogen	0 - 100 vol%
	Argon	0 - 100 vol%
Mathema	Air	0 - 100 vol%
weinane	Nitrogen	0 - 100 vol%
Natural gas or natural gas + LPG	_	25 - 50 MJ/m <sup>3</sup> Gross 0°C
	_	22 - 45 MJ/m <sup>3</sup>

Anesthetic gas specification (gases detectable as standard)

#### **Selection Examples**

In oxygen	
	Chamber length: 24 mm Halothane Isoflurane (vol%) We want to measure 3 types of gases via automatic suction using the built-in pump! Automatic Chamber length: Customized suction type 24mm Specification FI-8000 TYPE P - 24 - 99
In air	
	Chamber length: 48 mm Methyl Methyl Toluene (%LEL) Ethyl acetate (%LEL) (%LEL) Ethyl acetate (%LEL)

Chamber length 48 mm		
Measurement target gas	Base gas	Measurement range
Sulfuryl fluoride	Air	0 - 200 g/m <sup>3</sup>
Propylene oxide	Air	0 - 10 vol%
	Air	0 - 200 g/m³
Methyl bromide	Air	0 - 5 vol%
Methyl iodide	Air	0 - 200 g/m <sup>3</sup>
Phosphine	Air	0 - 50 g/m³
Hydrogen cyanide	Air	0 - 200 g/m³
Acetone	Air	0 - 100 %LEL
	Air	0 - 100 %LEL
Ammonia	Air	0 - 100 vol%
	Nitrogen	0 - 100 vol%
	Air	0 - 100 %LEL
Isobutane	Air	0 - 10 vol%
	Nitrogen	0 - 100 %LEL
Isopropyl alcohol	Air	0 - 100 %LEL
Carbon monoxide	Air	0 - 100 vol%
Ethyl alcohol	Air	0 - 100 %LEL
Ethylbenzene	Nitrogen	0 - 100 %LEL
	Air	0 - 100 %LEL
Ethylene	Air	0 - 20 vol%
	Nitrogen	0 - 100 %LEL
Ethylene chloride	Air	0 - 100 %LEL
	Air	0 - 100 %LEL
Xylene	Nitrogen	0 - 100 %LEL
Ethyl acetate	Air	0 - 100 %LEL
Butyl acetate	Air	0 - 100 %LEL
	Nitrogen	0 - 100 vol%
Oxygen	Argon	0 - 100 vol%
Dioxolane	Air	0 - 100 %LEL
Dichloroethane	Nitrogen	0 - 100 %LEL
	Air	0 - 100 %LEL
	Air	0 - 50 vol%
Hydrogen	Nitrogen	0 - 100 %LEL
	Argon	0 - 100 %LEL
	Argon	0 - 50 vol%
0	Air	0 - 100 %LEL
Styrene	Nitrogen	0 - 100 %LEL
Nitrogen	Argon	0 - 100 vol%
Tetrahydrofuran	Air	0 - 100 %LEL
Tetrafluoropropene	Air	0 - 100 %LEL
	Air	0 - 100 %LEL
Toluene	Nitrogen	0 - 100 %LEL
Normal butane	Nitrogen	0 - 100 %LEL
	Air	0 - 100 %LEL
Propane	Air	0 - 10 vol%
	Nitrogen	0 - 100 %LEL
Methanol	Air	0 - 100 %LEL
	Air	0 - 100 %LEL
	Air	0 - 50 vol%
Methane	Nitrogen	0 - 100 %LEL
	Argon	0 - 100 %LEL
Methyl isobutyl ketone	Air	0 - 100 %LEL
Methyl isopropyl ketone	Air	0 - 100 %LEL
Methyl ethyl ketone	Air	0 - 100 %LEL
	I	I

Fumigation gas specification (gases detectable as standard)

Specifications			
Model	FI-8000		
Measuring principle	Optical interferometric type		
Measurement target gases	See annexed table		
Reading accuracy	Indicated value ±3% (under identical conditions)*		
Туре		Туре А-□□-□□	
Sampling method	Automatic suction by built-in pump	Manual suction by handy aspirator	
Self-diagnosis function	Low battery voltage, low UV intensity, low contrast,	Low battery voltage, low UV intensity, low contrast, abnormal pressure, abnormal temperature	
Display	LCD digital display (7-segment numeric display + symbol + 20-segment character display x 2 lines)		
Displays	Measurement target gas name, measurement target gas concentration, measurement unit, battery level		
Power supply	Dry battery unit (AA alkaline dry battery × 3) or lithium-ion battery unit		
Continuous operating time	Dry battery unit: 12 hours or more (For a new dry battery, at 25°C, with no lighting) Lithium-ion battery unit: 18 hours or more (For a fully charged battery, at 25°C, with no lighting)	Dry battery unit: 16 hours or more (For a new dry battery, at 25°C, with no lighting) Lithium-ion battery unit: 24 hours or more (For a fully charged battery, at 25°C, with no lighting)	
Explosion-proofing	Intrinsically safe explosion-proof construction IECEx (Ex ia IIC T4 Ga), ATEX (II 1 G Ex ia IIC T4 Ga), Japan Ex (Ex ia IIC T4)		
Protection class	Compliant with IP67		
Certification	CE marking		
External dimensions	Approx. $154(W) \times 127(H) \times 81(D)mm$		
Mass	Approx. 1.1 kg (including the dry battery unit) / Approx. 1.2 kg (including the lithium-ion battery unit)		
Usage temperature / humidity range	-20°C to +50°C (no sudden changes), 95% RH or less (non-condensing)		
Data logger function	Maximum number of recorded items: 256 Communication method: IrDA		
Functions	Data logger, atmospheric pressure correction, temperature correction		
* The reading accuracy varies depending on the measurement target gas.			



### **RIKEN KEIKI Co., Ltd.**

2 -7-6 Azusawa, Itabashi-ku, Tokyo 174 - 8744, Japan

- Phone : +81-3-3966-1113
- Telefax : +81-3-3558-9110
- E-mail : intdept@rikenkeiki.co.jp

Web site : https://www.rikenkeiki.co.jp/english

\* The contents described in this catalog are subject to change without notice according to the performance improvement.

